



Infrared Refrigerant(R32) Sensor Module (Model: MH-Z1542B-R32)

User's Manual Version 1.0
Issue Date. 2023.03.01

Zhengzhou Winsen Electronics Technology Co., Ltd
ISO9001 Certificated Company

Statement

This manual's copyright belongs to Zhengzhou Winsen Electronics Technology Co., LTD. Without the written permission, any part of this manual shall not be copied, translated, stored in database or retrieval system, also can't spread through electronic, copying, record ways.

Thanks for purchasing our product. In order to let customers use it better and reduce the faults caused by misuse, please read the manual carefully and operate it correctly in accordance with the instructions. If users disobey the terms or remove, disassemble, change the components inside of the sensor, we shall not be responsible for the loss.

The specific such as color, appearance, sizes &etc., please in kind prevail.

We are devoting ourselves to products development and technical innovation, so we reserve the right to improve the products without notice. Please confirm it is the valid version before using this manual. At the same time, users' comments on optimized using way are welcome.

Please keep the manual properly, in order to get help if you have questions during the usage in the future.

Zhengzhou Winsen Electronics Technology CO., LTD.

MH-Z1542B-R32 Refrigerant Sensor Module

Profile

MH-Z1542B refrigerant (R32) sensor is a smart infrared type sensor, using non-dispersive infrared (NDIR) principle to detect the existence of refrigerant, with good selectivity and non-oxygen dependent. It is developed by the tight integration of mature infrared absorbing gas detection technology, precision optical circuit design and superior circuit design. It is a compact high performance sensor made by combining mature infrared gas detection technology with micro machining and sophisticated circuit design. It is easy to use and can be directly to replace the catalytic type sensor.



Main Features

- *High sensitivity, high resolution, fast response
- *UART output
- *Temperate compensation, excellent linear output, good stability, long lifespan
- *Anti-water vapor interference, anti-poisoning, direct replacement for catalytic sensors

Main applications

- *HVAC
- *Industrial process and safety monitoring

Main parameters

Table1.

Model No.	MH-Z1542B-R32
Detection Gas	Refrigerant
Working voltage	3.6~5V DC
Average current	< 85mA
Detection Range	0~5.00% Vol
Interface level	3.0 V
Output signal	UART
Preheat time	3 min
Response Time	$T_{25} < 7$ s
Working temperature	-20 ~ 60 °C
Working humidity	0 ~ 95% RH (No condensation)
Sizes	32.9x22.3x11.9mm
Weight	35 g
Lifespan	> 15 years

Resolution

Table2.

Detection Gas	Formula	Detection Range	Resolution	Accuracy
R32	CH ₂ F ₂	0~50% LFL	1% LFL	± 3.75%F.S.

Dimensions




Fig1.sensor size

Pin Definition: Table3.

Pin	Pin Definition
Pin 1, 2, 5, 6, 7	Reserved
Pin 3	UART(TXD) 0~3.3V data output
Pin 4	UART(RXD) 0~3.3V data input
Pin 8	GND
Pin 9	Vin voltage input




Fig2. Sensor Pins

Notes

- The product should be calibrated termly, the suggested period is no longer than 6 months.
- Do not use the product in high dusty environment for long time.
- The product should be away from heat source and avoid direct sunlight or other heat radiation.
- The product should be used within requested voltage range

Zhengzhou Winsen Electronics Technology Co., Ltd

Add: No.299, Jinsuo Road, National Hi-Tech Zone, Zhengzhou
450001 China

Tel: +86-371-67169097/67169670

Fax: +86-371-60932988

E-mail: sales@winsensor.com

Website: www.winsen-sensor.com

